MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.	HMIS HAZARD RATING							
	HEALTH	0	0 = INSIGNIFICANT		3 = HIGH			
	FLAMMABILITY	1	1 = SLIGHT		4 = EXTREME			
	REACTIVITY	0	2= MODERATE					
SAFETEC OF AMERICA	TRANSPORTATION INFORMATION							
	PROPER SHIPPING	PROPER SHIPPING NAME Safetec Antibiotic O						
	HAZARD CLASS/PK	G. GRP.	Not Applicable	REF.	Not Applicable			
	IDENTIFICATION N	JMBER	Not Applicable	LABEL	None Required Ground			
SECTION 1 - PRODUCT / COMPANY IDENTIFICATION								
IDENTITY (AS USED ON LABEL AND LIST)					Page 1 of 2			
Safetec Antibiotic Ointment with Bacitracin								
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NUMBER							
Safetec of America, Inc.		(800) 255-392	4					
ADDRESS (NUMBER, STREET, P.O. BOX)		IMBER FOR INFORMAT	NFORMATION					
887 Kensington Ave.		(716) 895-182	2					
(CITY, STATE AND ZIP CODE)		DATE PREPARE)	Septem	ber 1, 2010			
Buffalo, NY 14215	SUPERSEDES			January 27, 2009				
SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION								
HAZARDOUS COMPONENTS	CAS # % (wt.) ACGIH TLV/TW/		TLV/TWA/STEL					
(SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))		(OPTIONAL)	PPM		MG/M ³			
Petrolatum USP	8009-03-8	Proprietary	None Establi	shed	None Established			
Bacitracin Zinc USP	1405-89-6	Prop`	None Establi	shed	None Established			

This product is not known to contain a substance subject to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR 372 at or above minimal amounts.

SECTION 3 - HEALTH HAZARD DATA ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EX	EMERGENCY AND FIRST AID PROCEDURES						
SKIN: May cause irritation. May cause skin discoloratio of the skin.	Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If material is hot, submerge injured area in cold water. If victim is severely burned, remove to a hospital immediately.						
INHALATION: This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product.		If vapor or mist is generated when the material is heated or handled, remove victim from exposure.					
EYES: This product is minimally irritating to the eyes upon direct contact.		Immediately flush eyes with copious amounts of water for at least 15 minutes or until irritation subsides. If material is hot, treat for thermal burns and take victim to hospital immediately.					
INGESTION: DO NOT INGEST. This product is practically non-toxic by ingestion. Laxative properties may result in abdominal cramps and diarrhea.		Do not induce vomiting due to aspiration hazard. If vomiting should occur, lower head below knees to avoid aspiration.					
HEALTH HAZARDS (ACUTE AND CHRONIC):	allergic reaction in sus Ingestion of product i	luce a dermal reaction in sensitive individuals. Chronic: Repeated or prolonged exposure may cause in in susceptible individuals. Repeated or prolonged exposure may produce chronic eye irritation. Induct in large quantities may produce a mild laxative effect. Repeated of prolonged inhalation can cause a or lipid granuloma of the lung.					
CARCINOGENICITY No additional information	NTP?		IARC MONOGRAPHS?	No	OSHA REGULATED?	No	

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)

Safetec Antibiotic Ointment with Bacitracin

Page 2 of 2

Date: January 27, 2009

SECTION 4 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED) FLAMMABLE LIMITS (% Volume in Air for Lowest Flashing Component)

Higher than 93.3°C (200°F) closed cup LEL: Not Available UEL: Not Available

EXTINGUISHING MEDIA

Use dry chemical, foam, or caborn dioxide.

SPECIAL FIRE FIGHTING PROCEDURES

Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS

Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

SECTION 5 - PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED

Contain spill immediately. Do not allow spill to enter sewers or watercourses. Small spills: Absorb with appropriate inert material such as sand, clay, etc. and dispose of into a suitable container. Large spills: Large spills can be picked up using vacuum pumps, shovels, buckets, or other means and placed in drums or other suitable containers.

WASTE DISPOSAL METHODS

Dispose of in accordance with Local, State, and Federal regulations. Products classified as non-hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260-299" for complete waste disposal regulations. Consult your Local, State, or Federal Environmental Protection Agency before disposing of any chemicals.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Handling: Avoid breathing vapors or mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Wash clothing prior to reuse. May be slippery when spilled. Storage: Do not transfer to unmarked containers. Store in closed containers away from heat, sparks, open flame, or oxidizing materials.

SECTION 6 - EXPOSURE CONTROLS/PERSONAL PROTECTION						
RESPIRATORY PROTECTION		VENTILATION LOCAL EXHAUST: Recommended				
Respiratory protection is not required under conditions or normal use. If vapor or mist is generated when the material is heated or handled, use a organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified.		MECHANICAL (GENERAL): Not required				
PROTECTIVE GLOVES	respirators must be MOSIT tertified.	EYE PROTECTION				
For prolonged or repeated exposures, us	e impervious gloves If handling hot	Not required for normal use. If material is handled such that it could be splashed into eyes, wear				
material use insulated protective gloves.	e impervious grovesi ii nanamig not	plastic face shield or splash-proof safety goggles.				
OTHER PROTECTIVE CLOTHING OR EC	DUIPMENT	WORK/HYGIENIC PRACTICES				
		Consumption of food and beverage should be avoided in work areas where hydrocarbons are				
Eye wash stations should be nearby and	ready for use.	present. Always wash hands and face with soap and water before eating, drinking, or smoking.				
SECTION 7 - PHYSICAL/CHEMICAL PROPERTIES						
BOILING POINT		SPECIFIC GRAVITY (WATER = 1)				
343°C (650°F)		0.86-0.87				
VAPOR PRESSURE (mm Hg)		MELTING POINT				
No data		51.7-54.4°C (125-130°F)				
VAPOR DENSITY (AIR = 1)		pH (1% solution in water)				
No data		No data				
SOLUBILITY IN WATER		EVAPORATION RATE (IPA = 1)				
		No data				
		% VOLATILES (BY VOLUME)				
White to off-white ointment		No data				
SECTION 8 - STABILITY AND REACTIVITY						
STABILITY	UNSTABLE:	CONDITIONS TO AVOID				
	STABLE: XXX	Heat and oxidizing				
INCOMPATIBILITIES (MATERIALS TO AVOID)						
Extreme heat, sparks, open flame and oxidizers.						
HAZARDOUS DECOMPOSITION OR BYPRODUCTS						
May give off fumes of carbon monoxide and carbon dioxide and other oxides generated during combustion.						
HAZARDOUS POLYMERIZATI	ON MAY OCCUR:	CONDITIONS TO AVOID				
,	WILL NOT OCCUR: XXX	Temperatures above 300°C				

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.

data sinced it at the minor of vehicle assumes no responsibility for injury caused by ashormal asc or any material even in reasonable surcey procedures are followed.